

Liquid tight connector



- Certificate: UL Listed
- Standard: UL 514B / CSA C22.2 No. 18.3
- Material: Die-cast zinc + plastic sealing
- Surface: Polished
- Application: Connect FMC conduit to electrical box

Available size

Trade size	Metric designator	Material	Type	Ref. No.
3/8"	12	Zinc	Straight / 90°	C3001
1/2"	16	Zinc	Straight / 90°	C3002
3/4"	21	Zinc	Straight / 90°	C3003
1"	27	Zinc	Straight / 90°	C3004
1-1/4"	35	Zinc	Straight / 90°	C3005
1-1/2"	41	Zinc	Straight / 90°	C3006
2"	53	Zinc	Straight / 90°	C3007
2-1/2"	63	Zinc	Straight / 90°	C3008
3"	78	Zinc	Straight / 90°	C3009
4"	103	Zinc	Straight / 90°	C3010

Liquid tight connector with insulated throat



- Certificate: UL Listed
- Standard: UL 514B / CSA C22.2 No. 18.3
- Material: Die-cast zinc + plastic sealing
- Surface: Polished
- Application: Connect FMC conduit to electrical box

Available size

Trade size	Metric designator	Material	Type	Ref. No.
3/8"	12	Zinc	Straight / 90°	C3011
1/2"	16	Zinc	Straight / 90°	C3012
3/4"	21	Zinc	Straight / 90°	C3013
1"	27	Zinc	Straight / 90°	C3014
1-1/4"	35	Zinc	Straight / 90°	C3015
1-1/2"	41	Zinc	Straight / 90°	C3016
2"	53	Zinc	Straight / 90°	C3017
2-1/2"	63	Zinc	Straight / 90°	C3018
3"	78	Zinc	Straight / 90°	C3019
4"	103	Zinc	Straight / 90°	C3020