

UL framed LED exit sign



- Certificate: UL listed
- Standard: UL 924, OSHA
- Material: Steel or ABS frame, acrylic panel
- Feature: 100 ft viewing distance
- Temperature: -10°C to 50°C
- Mounting: Wall, side, or ceiling



Available size

Color	Configuration	Pictograms	Light source	Power	Dual voltage	Backup battery	Ref. No.
Green	Single face	EXIT	LED	8W	AC 120V / 277V	≥ 180 min	C7101
Green	Single face	Running man + arrow	LED	8W	AC 120V / 277V	≥ 180 min	C7102
Green	Double face	Running man + arrow	LED	8W	AC 120V / 277V	≥ 180 min	C7103

UL framed compact LED exit sign



- Certificate: UL listed
- Standard: UL 924, OSHA
- Material: ABS housing, acrylic panel
- Feature: 100 ft viewing distance, removeable directional arrow
- Temperature: -10°C to 50°C
- Mounting: Wall, side, or ceiling



Available size

Color	Configuration	Pictograms	Light source	Power	Dual voltage	Backup battery	Ref. No.
Green	Single face	EXIT + arrow	LED	8W	AC 120V / 277V	≥ 180 min	C7201
Green	Double face	EXIT + arrow	LED	8W	AC 120V / 277V	≥ 180 min	C7202
Red	Single face	EXIT + arrow	LED	8W	AC 120V / 277V	≥ 180 min	C7203
Red	Double face	EXIT + arrow	LED	8W	AC 120V / 277V	≥ 180 min	C7204