

Dry chemical fire extinguisher

Dry chemical (Dry powder) fire extinguisher is the most common hand-held portable extinguisher. It is suitable for fires Class A, B and C involving combustible solids, flammable liquids and gases.



- Certificate: UL Listed
- Standard: ANSI / UL 299, ANSI / UL 711
- Fire rating: Class A, B and C fire
- Marine type: Yes, B.C Size I
- Temperature: -40°C to 49°C
- W. pressure: 195 psi
- Surface: Red powder coating

Main parts and material

Cylinder	Deep drawn steel	Extinguishing agent	ABC powder, ammonium phosphate-based chemicals
Cylinder valve	Aluminum, with pressure gauge and SS handle	Hose assembly	Rubber, as UL 92

Available size

Capacity (lb)	UL rating	Dimension (inch)		Overall weight (lb)	Discharge time (sec.)	Ref. No.
		Cylinder dia.	Height			
2.5	1-A:10-B:C	3.5"	14.4"	5.7 Lbs	9	F7001
5.0	3-A:30-B:C	4.3"	17.3"	9.9 Lbs	14	F7002
10.0	4-A:60-B:C	5.5"	20.2"	18.0 Lbs	22	F7003
20.0	6-A:80-B:C	7.2"	23.6"	32.6 Lbs	23	F7004

Note: Wall hook or wall bracket is included for mounting.