

Double wheel operated fire monitor

Fire monitor is designed with large clear waterways to give a powerful, far-reaching stream for heavy duty fire application. It is supplied in fixed installation for one man operation, and the water flow and aim are adjustable.



- Certificate: FM Approved
- Standard: NFPA 1964
- Connection: Flanged as ANSI 150#
- Fire agent: Water, foam
- Rotation: Full 360° horizontal travel
- Waterway: Single full 2-3/4" or 3-1/4"
- Flow rate: Max 1250 GPM
- W. pressure: 200 psi
- Surface: Red powder coating



Main parts and material

Construction	Aluminum alloy	Master stream nozzle	Aluminum, fixed teeth or spinning teeth as option
Control	SS handwheel, double	twist lock	Brass and SS

Available size

Flow rate (GPM)	Waterway	Base inlet	Outlet	Vertical travel 135°		Rated operating pressure (psi)	Ref. No.
				Above	Below		
750	2-3/4" single	3" Flange	2-1/2"NH, M	90°	45°	200	F8301
750	2-3/4" single	4" Flange	2-1/2"NH, M	90°	45°	200	F8302
750	2-3/4" single	3" NPT, F	2-1/2"NH, M	90°	45°	200	F8303
1250	3-1/4" single	3" Flange	2-1/2"NH, M	90°	45°	200	F8304
1250	3-1/4" single	4" Flange	2-1/2"NH, M	90°	45°	200	F8305