


## Rack and reel fire hose

Rack and reel fire hose is intended for interior fire protection purpose of occupant use, lightweight and compact. It is a part of fire hose rack assembly for hose station, folded on a pin rack or coiled on a reel, ready for use.



- Certificate: UL Listed / FM Approved
- Standard: UL 219, NFPA 1961 / 1962
- Feature: Occupant use, lightweight
- Color: White, standard
- Avail. coating: Impregnated yellow, red, etc.
- Temperature: -40°C to 70°C



### Main parts and material

|                 |   |                      |  |
|-----------------|---|----------------------|--|
| <b>Lining</b>   | TPU (Thermoplastic polyurethane)        | <b>Single jacket</b> | 100% virgin filament polyester for warp and filler threads |
| <b>Coupling</b> | Brass / aluminum, rocker lug swivel, NH | <b>Packing</b>       | Folded, or rolled  |

### Available size

| Size   | Type          | Lining | Length (feet) | Service pressure (psi) | Proof pressure (psi) | Burst pressure (psi) | Ref. No.   |
|--------|---------------|--------|---------------|------------------------|----------------------|----------------------|------------|
| 1-1/2" | Single jacket | TPU    | 50 / 75 / 100 | 250                    | 500                  | 750                  | F4001 (UL) |
| 1-1/2" | Single jacket | TPU    | 50 / 75 / 100 | 250                    | 500                  | 750                  | F4002 (FM) |

**Note:** The couplings are pre-assembled on both ends of fire hose through expansion rings.