


K8.0 ECLH pendent sprinkler

K8.0 ECLH (Extended coverage light hazard) pendent sprinkler is designed for use in light hazard occupancies, and it provides max coverage area of 400 ft² (37.2 m²) as NFPA 13.



- Certificate: UL Listed / FM Approved
- Standard: UL 199, NFPA 13
- Feature: K8.0 (K115), ECLH, min spacing 8 ft
- W. pressure: 175 psi
- T. pressure: 500 psi, factory hydrostatic test
- O. pressure: Min 7 psi
- Surface: Rough brass / chrome plated / white painted, etc.



Main parts and material

Deflector	Bronze / brass	Heat responsive element	Glass bulb, 3 mm diameter
Frame	Brass / bronze	Sealing assembly	Beryllium nickel spring + Teflon tape

Available size

Type	Nominal K-Factor	Response type		Temperature rating	Connection	Working pressure (psi)	Ref. No.
		UL	FM				
ECLH pendent	K5.6 (K80)	QR	QR	135°F (57°C)	3/4", NPT or BSPT	175	S2601
ECLH pendent	K5.6 (K80)	SR or QR	QR	155°F (68°C)	3/4", NPT or BSPT	175	S2602
ECLH pendent	K5.6 (K80)	SR or QR	QR	175°F (79°C)	3/4", NPT or BSPT	175	S2603
ECLH pendent	K5.6 (K80)	QR	/	200°F (93°C)	3/4", NPT or BSPT	175	S2604 (UL)
ECLH recessed pendent	K5.6 (K80)	QR	QR	135°F (57°C)	3/4", NPT or BSPT	175	S2605
ECLH recessed pendent	K5.6 (K80)	SR or QR	QR	155°F (68°C)	3/4", NPT or BSPT	175	S2606
ECLH recessed pendent	K5.6 (K80)	SR or QR	QR	175°F (79°C)	3/4", NPT or BSPT	175	S2607
ECLH recessed pendent	K5.6 (K80)	QR	/	200°F (93°C)	3/4", NPT or BSPT	175	S2608 (UL)

Note:

1. As UL rule, it is SR or QR sprinkler at max coverage area (ft x ft) 16 x 16, 18 x 18, and 20 x 20, with different temperature rating.
2. As FM rule, it is only QR sprinkler at max coverage area (ft x ft) 16 x 16, 18 x 18, and 20 x 20.
3. For recessed sprinkler, it is assembled with a specified recessed escutcheon which provides adjustment up to 3/4" (19.1 mm).