


Bronze OS&Y gate valve




- Certificate: UL Listed / FM Approved
- Standard: UL 262
- Material: Bronze
- Connection: Thread, NPT / BSPT
- Temperature: -20°C to 180°C
- W. pressure: 175 psi
- Surface: Rough bronze



Available size

Size		Dimension (mm)			Connection	Working pressure (psi)	Ref. No.
Inch	DN	L	H min	H max			
1/2"	15	59	128	146	NPT / BSPT	175	VC3101
3/4"	20	61	145	167	NPT / BSPT	175	VC3102
1"	25	73	163	192	NPT / BSPT	175	VC3103
1-1/4"	32	79	189	226	NPT / BSPT	175	VC3104
1-1/2"	40	84	213	259	NPT / BSPT	175	VC3105
2"	50	90	248	304	NPT / BSPT	175	VC3106

Bronze NRS gate valve



- Certificate: ISO
- Material: Bronze
- Connection: Thread, BSPT / NPT
- Temperature: -20°C to 180°C
- W. pressure: PN 20, or PN 25 (Only BSPT)
- Surface: Rough bronze



Available size

Size		Dimension (mm)			Connection	Working pressure	Ref. No.
Inch	DN	L	H	D			
1/2"	15	50	76	55	BSPT / NPT	PN 20 / 25	VC3201
3/4"	20	54	84	55	BSPT / NPT	PN 20 / 25	VC3202
1"	25	60	94	60	BSPT / NPT	PN 20 / 25	VC3203
1-1/4"	32	68	109	72	BSPT / NPT	PN 20 / 25	VC3204
1-1/2"	40	73	120	72	BSPT / NPT	PN 20 / 25	VC3205
2"	50	87	145	80	BSPT / NPT	PN 20 / 25	VC3206
2-1/2"	65	103	180	100	BSPT / NPT	PN 20	VC3207
3"	80	116	208	110	BSPT / NPT	PN 20	VC3208
4"	100	140	255	130	BSPT / NPT	PN 20	VC3209