



Check snoot

- Certificate: UL listed
- Standard: NFPA 14 / NFPA 1963
- Feature: Prevent backflow for inlet FDC
- W. pressure: 175 psi
- Surface: Rough / chrome plated

Available size

Size	Material	Check type	Inlet	Outlet	Working pressure (psi)	Ref. No.
2-1/2" x 3"	Brass	Clapper	2-1/2" FNH, swivel	3" NPT, F	175	F2301 (UL)
2-1/2" x 3"	Brass	Clapper	2-1/2" FNH, swivel	3" NPT, M	175	F2302 (UL)
2-1/2" x 3"	Brass	Spring	2-1/2" FNH, swivel	3" NPT, F	175	F2303 (ISO)
2-1/2" x 3"	Brass	Spring	2-1/2" FNH, swivel	3" NPT, M	175	F2304 (ISO)



Open snoot (Open adapter)

- Certificate: ISO
- Standard: NFPA 14 / NFPA 1963
- Feature: Inlet or outlet FDC component
- W. pressure: 175 psi
- Surface: Rough / chrome plated

Available size

Size	Material	Connection	Inlet	Outlet	Working pressure (psi)	Ref. No.
2-1/2" x 2-1/2"	Brass	Swivel inlet	2-1/2" NH, F	2-1/2" NPT, F	175	F2401
2-1/2" x 3"	Brass	Swivel inlet	2-1/2" NH, F	3" NPT, F	175	F2402
2-1/2" x 2-1/2"	Brass	Swivel inlet	2-1/2" NH, F	2-1/2" NPT, M	175	F2403
2-1/2" x 3"	Brass	Swivel inlet	2-1/2" NH, F	3" NPT, M	175	F2404
2-1/2" x 2-1/2"	Brass	Solid hex	2-1/2" NPT, F	2-1/2" NH, M	175	F2405
2-1/2" x 3"	Brass	Solid hex	3" NPT, F	2-1/2" NH, M	175	F2406