

Exposed fire department inlet connection (FDC)

Fire department inlet connection (Siamese connection) is used as an auxiliary connection to supplement water from its inlet. For exposed FDC, the body and inlet are found on buildings' outside wall for easy access by firefighter.



Main parts and material


Body	Cast brass, pin lug swivel inlet and clapper	Clapper	Brass, single swing or individual drop	
Plug	Brass, pin lug, with chain	Wall plate	Brass, special lettering for identification	


Available size

Size	Way of inlet	Clapper	Body pattern	Inlet	Outlet	Working pressure (psi)	Ref. No.
2-1/2" x 4"	2-way	Single	Straight	(2) 2-1/2" NH, F	4" NPT, F	300	F0301 (UL/FM)
2-1/2" x 4"	2-way	Single	Angle	(2) 2-1/2" NH, F	4" NPT, F	300	F0302 (UL/FM)
2-1/2" x 4"	2-way	Double	Straight	(2) 2-1/2" NH, F	4" NPT, F	175	F0303 (UL/FM)
2-1/2" x 4"	2-way	Double	Angle	(2) 2-1/2" NH, F	4" NPT, F	175	F0304 (UL/FM)
2-1/2" x 6"	2-way	Double	Straight	(2) 2-1/2" NH, F	6" NPT, F	175	F0305 (UL)
2-1/2" x 6"	2-way	Double	Angle	(2) 2-1/2" NH, F	6" NPT, F	175	F0306 (UL)
3" x 4"	2-way	Double	Straight	(2) 3" NH, F	4" NPT, F	300	F0307 (UL)
3" x 4"	2-way	Double	Angle	(2) 3" NH, F	4" NPT, F	300	F0308 (UL)



- · Certificate: UL listed / FM Approved
- · Standard:
- ANSI / UL 405
- · Feature: Exposed type inlet
- W. pressure: 300 / 175 psi
- · Surface: Rough / polished / chrome plated





VdS E

((ISO))



Exposed fire department inlet connection (FDC)

Available size

Size	Way of inlet	Clapper	Body pattern	Inlet	Outlet	Working pressure (psi)	Ref. No.
3" x 6"	2-way	Double	Straight	(2) 3" NH, F	6" NPT, F	175	F0309 (UL)
3" x 6"	2-way	Double	Angle	(2) 3" NH, F	6" NPT, F	175	F0310 (UL)
2-1/2" x 6"	2-way	Double	Straight	(2) 2-1/2" NH, F	6" NPT, F	175	F0311 (UL/FM)
2-1/2" x 6"	2-way	Double	Angle	(2) 2-1/2" NH, F	6" NPT, F	175	F0312 (UL/FM)
3" x 4"	2-way	Double	Straight	(2) 3" NH, F	4" NPT, F	175	F0313 (UL/FM)
3" x 4"	2-way	Double	Angle	(2) 3" NH, F	4" NPT, F	175	F0314 (UL/FM)
3" x 6"	2-way	Double	Straight	(2) 3" NH, F	6" NPT, F	175	F0315 (UL/FM)
3" x 6"	2-way	Double	Angle	(2) 3" NH, F	6" NPT, F	175	F0316 (UL/FM)
2-1/2" x 4"	3-way	Three	Straight	(3) 2-1/2" NH, F	4" NPT, F	175	F0317 (ISO)
2-1/2" x 4"	3-way	Three	Angle	(3) 2-1/2" NH, F	4" NPT, F	175	F0318 (ISO)
2-1/2" x 6"	3-way	Three	Straight	(3) 2-1/2" NH, F	6" NPT, F	175	F0319 (ISO)
2-1/2" x 6"	3-way	Three	Angle	(3) 2-1/2" NH, F	6" NPT, F	175	F0320 (ISO)

U (LPCB) 😵 🔽 🕻 🦉

Note: The FDC assembly includes 3 parts: FDC body, plug (cap) with chain, and wall plate.

