


# Single jacket fire hose

Single jacket fire hose is designed for exterior municipal and industrial use, suitable for hydrant water transfer, wash down, mill discharge service. It is flexible, abrasion resistant, mold and mildew resistant.



- Certificate: UL Listed / FM Approved
- Standard: UL 19, NFPA 1961 / 1962
- Feature: Single jacket, flexible
- Color: White, standard
- Avail. coating: Impregnated yellow, red, etc.
- Temperature: -40°C to 70°C



## Main parts and material

<b>Lining</b>	EPDM / TPU	<b>Single jacket</b>	100% high tenacity polyester for warp and filler threads
<b>Coupling</b>	Brass / aluminum, rocker lug swivel, NH	<b>Packing</b>	Rolled

## Available size (Source 1 with UL or FM)

Size	Hose type	Lining	Length (feet)	Service pressure (psi)	Proof pressure (psi)	Burst pressure (psi)	Ref. No.
1-1/2"	Single jacket	EPDM	50 / 75 / 100	200	400	600	F4101 (UL)
2-1/2"	Single jacket	EPDM	50 / 75 / 100	200	400	600	F4102 (UL)
1-1/2"	Single jacket	EPDM	50 / 75 / 100	250	500	750	F4103 (FM)
1-3/4"	Single jacket	EPDM	50 / 75 / 100	250	500	750	F4104 (FM)
2"	Single jacket	EPDM	50 / 75 / 100	250	500	750	F4105 (FM)
2-1/2"	Single jacket	EPDM	50 / 75 / 100	250	500	750	F4106 (FM)

**Note:**

1. The couplings are pre-assembled on both ends of fire hose through expansion rings.
3. For F4101 and F4102, please refer to UL certificate (Cert No EX27792) as our TPMC brand, with model SJ EPDM 200PSI.

# Single jacket fire hose

## Available size (Source 2 with UL or FM)

Size	Hose type	Lining	Length (feet)	Service pressure (psi)	Proof pressure (psi)	Burst pressure (psi)	Ref. No.
2-1/2"	Single jacket	TPU	50 / 75 / 100	250	500	750	F4111 (UL)
1-1/2"	Single jacket	EPDM	50 / 75 / 100	250	500	750	F4112 (UL/FM)
1-3/4"	Single jacket	EPDM	50 / 75 / 100	250	500	750	F4113 (FM)
2-1/2"	Single jacket	EPDM	50 / 75 / 100	250	500	750	F4114 (UL/FM)

**Note:** The couplings are pre-assembled on both ends of fire hose through expansion rings.