

Lever operated fire monitor (Double waterway)

Fire monitor is designed with large clear waterways to give a powerful, far-reaching stream for heavy duty fire application. It is supplied in fixed installation for one man operation, and the water flow and aim are adjustable.



- Certificate: FM Approved
- Standard: NFPA 1964
- Connection: Flanged as ANSI 150#
- Fire agent: Water, foam
- Rotation: Full 360° horizontal travel
- Waterway: Dual full 2-1/2"
- Flow rate: Max 750 GPM
- W. pressure: 200 psi
- Surface: Red powder coating



Main parts and material

Construction	Corrosion resistant brass	Master stream nozzle	Brass, fixed teeth or spinning teeth as option
Control	SS Lever / handle rod / tiller	twist lock	Brass and SS

Available size

Flow rate (GPM)	Waterway	Base inlet	Outlet	Vertical travel 130°		Rated operating pressure (psi)	Ref. No.
				Above	Below		
750	2-1/2" double	2-1/2" Flange	2-1/2"NH, M	70°	60°	200	F8001 (FM)
750	2-1/2" double	3" Flange	2-1/2"NH, M	70°	60°	200	F8002 (FM)
750	2-1/2" double	4" Flange	2-1/2"NH, M	70°	60°	200	F8003 (FM)
750	2-1/2" double	6" Flange	2-1/2"NH, M	70°	60°	200	F8004 (FM)
750	2-1/2" double	2-1/2" NPT, F	2-1/2"NH, M	70°	60°	200	F8005 (ISO)