

## Water fire extinguisher

Fire extinguisher contains extinguishing medium which is expelled by the action of internal pressure and directed to combat a fire. For portable water fire extinguisher, it is a cost effective option for Class A fire risk.



- Certificate: BSI / LPCB Approved
- Standard: BS EN 3-7 / 3-8 / 3-10
- Fire rating: Class A fire
- Temperature: 5°C to 60°C
- W. pressure: 15 bar
- Test: 27 bar
- Surface: Red powder coating



### Main parts and material

<b>Cylinder</b>	Deep drawn steel, DC01 or DC04 to EN 10130	<b>Extinguishing medium</b>	Water, or water additive
<b>Control valve</b>	Brass, with pressure indicator	<b>Hose assembly</b>	Rubber, with hose retaining clip

### Available size

Capacity (L)	Extinguishing medium	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Ref. No.
			Cylinder dia.	Height			
3	Water+additive	13A	130	435	5.2	20	FE8301
6	Water+additive	27A	162	537	9.6	45	FE8302
6	Water	13A	162	537	9.6	45	FE8303
9	Water	21A	182	620	14	22	FE8304

**Note:** Fire extinguisher bracket is included.