

Steel IMC coupling


Steel IMC (intermediate metal conduit) coupling is made from the same material of straight IMC conduit, and it connects the same size of the conduit together. Both the outside and inside surfaces are galvanized for corrosion resistance.





· Certificate: ISO

Standard: UL 1242 / ANSI C80.6
Material: Carbon steel strip
Surface: Hot dip galvanized



Available size

| Trade size | Metric designator | OD | Length | Ref. No. |
|------------|----------------------|--------|--------|----------|
| | | D (mm) | L (mm) | |
| 1/2" | 16 | 25.7 | 41.3 | C1501 |
| 3/4" | 21 | 31.8 | 41.7 | C1502 |
| 1" | 27 | 38.7 | 50.0 | C1503 |
| 1-1/4" | 35 | 47.5 | 51.6 | C1504 |
| 1-1/2" | 41 | 54.7 | 52.4 | C1505 |
| 2" | 53 | 67.3 | 54.0 | C1506 |
| 2-1/2" | 63 | 82.6 | 81.0 | C1507 |
| 3" | 78 | 98.3 | 84.1 | C1508 |
| 4" | 103 | 123.8 | 89.3 | C1509 |

Note:

1. OD tolerance: OD 1/2" ~ 1", - 0.40mm (0.016"); OD 1-1/4" ~ 6", -1%.

 $2. \, \hbox{All couplings shall have straight-tapped threads}.$











