


Steel RMC conduit

Steel RMC conduit (rigid metal conduit) is rigid, heavy-walled, threaded ERW tube used as a metal raceway for protecting and routing of electrical wiring. It is permitted in all atmospheric conditions as its excellent corrosion resistance.



- Certificate: UL Listed
- Standard: UL 6 / ANSI C80.1
- Material: Carbon steel strip
- Surface: Hot dip galvanized



Available size

Trade size	Metric designator	OD	Thickness	Length	Ref. No.
		D (mm)	T (mm)	L (m)	
1/2"	16	21.3	2.6	3.05 (10 ft)	C1601
3/4"	21	26.7	2.7	3.05 (10 ft)	C1602
1"	27	33.4	3.2	3.05 (10 ft)	C1603
1-1/4"	35	42.2	3.4	3.05 (10 ft)	C1604
1-1/2"	41	48.3	3.5	3.05 (10 ft)	C1605
2"	53	60.3	3.7	3.05 (10 ft)	C1606
2-1/2"	63	73.0	4.9	3.05 (10 ft)	C1607
3"	78	88.9	5.2	3.05 (10 ft)	C1608
4"	103	114.3	5.7	3.05 (10 ft)	C1609
5"	129	141.3	6.2	3.05 (10 ft)	C1610
6"	155	168.3	6.8	3.05 (10 ft)	C1611

Note:

1. OD tolerance: OD 1/2" ~ 1-1/2", $\pm 0.38\text{mm}$ (0.015"); OD 2" ~ 6", $\pm 1\%$.
2. thickness tolerance: $\pm 12.5\%$.
3. Length tolerance: $\pm 6.35\text{mm}$ (1/4") without coupling.