


# Liquid-tight flexible metal conduit

Liquid-tight flexible metal conduit has a smooth PVC jacket over an inner flexible metal core. It is sunlight resistant and suitable for use outdoors in wet, dry, or oily locations.



- Certificate: UL Listed
- Standard: UL 360 / CSA C22.2 No.56
- Material: Galv. carbon steel + PVC jacket
- Temperature: -20°C ~ 105°C dry / 60°C wet / 70°C oil resistant
- IP rating: IP 40 / IP 66
- Color: Grey, blue, or customized



## Available size

Trade size	Metric designator	Outer diameter (mm)		Inner diameter (mm)		Bending radius (mm)	Ref. No.
		min	max	min	max		
3/8"	12	17.5	18.0	12.29	12.80	61	C2001
1/2"	16	20.8	21.3	15.80	16.31	93	C2002
3/4"	21	25.2	26.7	20.83	21.34	118	C2003
1"	27	32.8	33.4	26.44	27.08	175	C2004
1-1/4"	35	41.4	42.2	35.05	35.81	213	C2005
1-1/2"	41	47.4	48.3	40.01	40.64	239	C2006
2"	53	59.4	60.3	51.31	51.94	293	C2007
2-1/2"	63	72.1	73.0	62.99	63.63	381	C2008
3"	78	87.9	88.9	77.98	78.74	455	C2009
4"	103	113.3	114.3	101.60	102.62	620	C2010