


Adjustable fog nozzle

Adjustable fog nozzle (Portable spray nozzle) is normally used as rack nozzle with fire hose mounted on standpipe systems. It is adjustable by rotational control from wide fog, narrow fog, straight stream, to shut-off.



- Certificate: UL Listed / FM Approved
- Standard: UL 401, NFPA 14 / 1964
- Fire type: Class A and B
- Fire agent: Water
- Material: Cast brass / polycarbonate
- Feature: Adjustable, shut-off feature
- Surface: Rough / polished / chrome plated



Main parts and material

Barrel / base	Forged brass / polycarbonate	Stem (T-head)	Forged brass / polycarbonate
Packing	Synthetic rubber	Rubber bumper	NBR

Available size

Size	Material	Inlet	Max inlet pressure (psi)	Rated operating pressure (psi)	Rated flow (gpm)	Ref. No.
1-1/2"	Cast brass	1-1/2" NH, F	200	100	130	F5001 (UL)
1-1/2"	Cast brass	1-1/2" NH, F	200	100	110	F5002 (UL/FM)
1-1/2"	Polycarbonate	1-1/2" NH, F	175	100	115	F5003 (UL/FM)
2-1/2"	Cast brass	2-1/2" NH, F	200	100	280	F5004 (UL)
2-1/2"	Cast brass	2-1/2" BS336	200	100	280	F5005 (UL)
1-1/2"	Cast brass	1-1/2" NH, F	200	100	90	F5006 (ISO)
2-1/2"	Cast brass	2-1/2" NH, F	200	100	200	F5007 (ISO)
2-1/2"	Polycarbonate	2-1/2" NH, F	175	100	273	F5008 (ISO)