


Alarm pressure switch with retard





- Certificate: UL Listed / FM Approved
- Standard: Comply to NFPA 13, 13D, 13R, 72
- Valve type: Wet sprinkler system alarm check valve
- Contact ratings: 10A at 125/250VAC, 2.5A at 30VDC
- Temperature: -40°C to 60°C
- Enclosure: IP54
- Surface: Corrosion resistant finish



Available size

Switch	Time delay setting (Sec.)	Factory setting (psi)	Connection	Max operating pressure (psi)	Ref. No.
Two SPDT	0- 65	5-8	1/2" NPT, male	200	V8701
Two SPDT	0- 90	4-8	1/2" NPT, male	175	V8702

Electrically operated solenoid valve



- Certificate: UL Listed
- Standard: UL 429
- Material: Brass body, EPDM diaphragm, SS304 spring
- Feature: Normally closed, pilot operated, 2-way
- Temperature: -10°C to 120°C
- W. pressure: 300 psi
- Surface: Rough brass



Available size

Type	Electrical ratings	Pressure range (psi)	Connection	Working pressure (psi)	Ref. No.
Pilot operated	24VDC / 10W	7.5 ~ 300	1/2", NPT / BSPT	300	V8801
Pilot operated	24VDC / 22W	20 ~ 300	1/2", NPT / BSPT	300	V8802