


Brass swing check valve




- Certificate: ISO
- Material: Brass
- Connection: Thread, BSPT / NPT
- Temperature: -20°C to 150°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass



Available size

| Size | | Dimension (mm) | | Connection | Working pressure | Ref. No. |
|--------|-----|----------------|-----|------------|------------------|----------|
| Inch | DN | L | H | | | |
| 1/2" | 15 | 50 | 35 | BSPT / NPT | PN 16 | VC1301 |
| 3/4" | 20 | 60 | 40 | BSPT / NPT | PN 16 | VC1302 |
| 1" | 25 | 74 | 47 | BSPT / NPT | PN 16 | VC1303 |
| 1-1/4" | 32 | 84 | 53 | BSPT / NPT | PN 16 | VC1304 |
| 1-1/2" | 40 | 94 | 60 | BSPT / NPT | PN 16 | VC1305 |
| 2" | 50 | 114 | 70 | BSPT / NPT | PN 16 | VC1306 |
| 2-1/2" | 65 | 146 | 86 | BSPT / NPT | PN 16 | VC1307 |
| 3" | 80 | 165 | 102 | BSPT / NPT | PN 16 | VC1308 |
| 4" | 100 | 192 | 122 | BSPT / NPT | PN 16 | VC1309 |

Brass spring check valve



- Certificate: ISO
- Material: Brass, silicone rubber disc
- Connection: Thread, BSPT / NPT
- Temperature: -20°C to 150°C
- W. pressure: PN 16 (1.6 MPa)
- Start pressure: 0.4 bar (0.04 MPa)
- Surface: Rough brass



Available size

| Size | | L (mm) | Connection | Working pressure | Ref. No. |
|--------|-----|--------|------------|------------------|----------|
| Inch | DN | | | | |
| 1/2" | 15 | 59 | BSPT / NPT | PN 16 | VC1401 |
| 3/4" | 20 | 67 | BSPT / NPT | PN 16 | VC1402 |
| 1" | 25 | 74 | BSPT / NPT | PN 16 | VC1403 |
| 1-1/4" | 32 | 86 | BSPT / NPT | PN 16 | VC1404 |
| 1-1/2" | 40 | 93 | BSPT / NPT | PN 16 | VC1405 |
| 2" | 50 | 108 | BSPT / NPT | PN 16 | VC1406 |
| 2-1/2" | 65 | 115 | BSPT / NPT | PN 16 | VC1407 |
| 3" | 80 | 128 | BSPT / NPT | PN 16 | VC1408 |
| 4" | 100 | 151 | BSPT / NPT | PN 16 | VC1409 |