


# Freestanding fire department outlet connection (FDC)

Freestanding fire department outlet connection (Freestanding hydrant) is used as an auxiliary connection to obtain water from its outlet. For freestanding FDC, it normally stands apart from the building and nears a sidewalk.



- Certificate: FM Approved
- Standard: NFPA 14
- Feature: Freestanding type outlet
- W. pressure: 175 psi
- Surface: Rough / polished / chrome plated



## Main parts and material

<b>Body</b>	Cast brass, hose thread outlet	<b>Cover sleeve</b>	Brass polished tube, height 18"
<b>Cap</b>	Brass, pin lug, with chain	<b>Wall plate</b>	Brass, special lettering for identification

## Available size

Size	Way of outlet	Body pattern	Inlet	Outlet	Working pressure (psi)	Ref. No.
4" x 2-1/2"	2-way	Angle	4" NPT, F	(2) 2-1/2" NH, M	175	F0901 (FM)
6" x 2-1/2"	2-way	Angle	6" NPT, F	(2) 2-1/2" NH, M	175	F0902 (FM)
6" x 2-1/2"	3-way	Angle	6" NPT, F	(3) 2-1/2" NH, M	175	F0903 (ISO)
6" x 2-1/2"	4-way	Angle	6" NPT, F	(4) 2-1/2" NH, M	175	F0904 (ISO)