


K8.0 dry quick response HSW sprinkler

Dry sprinkler is mainly used to protect areas subject to freezing temperatures. The sprinkler is secured in an extension nipple that has a seal at the inlet end to prevent water from entering the nipple until the sprinkler operates.



- Certificate: UL Listed
- Standard: UL 199, NFPA 13
- Feature: K8.0 (K115), dry, HSW
- W. pressure: 175 psi
- T. pressure: 500 psi, factory hydrostatic test
- O. pressure: Min 7 psi
- Surface: Rough brass / chromed (Sprinkler)
Signal white / chromed (Escutcheon)



Main parts and material

Deflector / frame	Brass or SS	Heat responsive element	Glass bulb, 3 mm diameter
Nipple (Tube)	Galvanized steel pipe for outer tube, and SS for inner tube	Escutcheon	Carbon steel or SS

Available size

Type	Nominal K-Factor	Response type	Temperature rating	Order length (A)	Connection	Working pressure (psi)	Ref. No.
Dry horizontal sidewall (HSW)	K8.0 (K115)	QR	135°F (57°C)	4-1/2" to 48"	1", NPT or BSPT	175	S5901 (UL)
Dry horizontal sidewall (HSW)	K8.0 (K115)	QR	155°F (68°C)	4-1/2" to 48"	1", NPT or BSPT	175	S5902 (UL)
Dry horizontal sidewall (HSW)	K8.0 (K115)	QR	175°F (79°C)	4-1/2" to 48"	1", NPT or BSPT	175	S5903 (UL)
Dry horizontal sidewall (HSW)	K8.0 (K115)	QR	200°F (93°C)	4-1/2" to 48"	1", NPT or BSPT	175	S5904 (UL)
Dry horizontal sidewall (HSW)	K8.0 (K115)	QR	286°F (141°C)	4-1/2" to 48"	1", NPT or BSPT	175	S5905 (UL)
Dry recessed horizontal sidewall (HSW)	K8.0 (K115)	QR	135°F (57°C)	4" to 48"	1", NPT or BSPT	175	S5906 (UL)
Dry recessed horizontal sidewall (HSW)	K8.0 (K115)	QR	155°F (68°C)	4" to 48"	1", NPT or BSPT	175	S5907 (UL)
Dry recessed horizontal sidewall (HSW)	K8.0 (K115)	QR	175°F (79°C)	4" to 48"	1", NPT or BSPT	175	S5908 (UL)
Dry recessed horizontal sidewall (HSW)	K8.0 (K115)	QR	200°F (93°C)	4" to 48"	1", NPT or BSPT	175	S5909 (UL)
Dry recessed horizontal sidewall (HSW)	K8.0 (K115)	QR	286°F (141°C)	4" to 48"	1", NPT or BSPT	175	S5910 (UL)

- Note:**
1. Dry sprinklers are furnished based on Order length (A) as measured per drawing. After the measurement is taken, round it to the nearest 1/4" increment.
 2. It is available with other mounting type, such as flush, sleeve & skirt, extended sleeve & skirt (deep), etc.