


## K16.8 ESFR upright sprinkler

K16.8 ESFR (Early suppression fast response) sprinkler is designed to offer extremely fast response for specific high-challenge fire hazards. It discharges large volumes of water in short time to suppress rather than control fire.



- Certificate: FM Approved
- Standard: UL 199, NFPA 13
- Feature: K16.8 (K242), ESFR, upright
- W. pressure: 175 psi
- T. pressure: 500 psi, factory hydrostatic test
- O. pressure: Refer to NFPA 13 / FM spec.
- Surface: Rough brass



### Main parts and material

<b>Deflector</b>	Copper	<b>Heat responsive element</b>	Fusible alloy, beryllium nickel link assembly
<b>Frame</b>	Brass	<b>Sealing assembly</b>	Nickel alloy spring + Teflon tape

### Available size (Source 1 with FM)

Type	Nominal K-Factor	Response type	Temperature rating	Connection	Working pressure (psi)	Ref. No.
ESFR upright	K16.8 (K242)	ESFR	165°F (74°C)	3/4", NPT or BSPT	175	S6301 (FM)

### Available size (Source 2 with ISO)

Type	Nominal K-Factor	Response type	Temperature rating	Connection	Working pressure (psi)	Ref. No.
ESFR pendent	K16.8 (K242)	ESFR	165°F (74°C)	3/4", NPT or BSPT	175	S6321 (ISO)