


Window sprinkler (Outside sprinkler)

Window sprinkler (Outside sprinkler) is an open type nozzle, and it provides a flat 180° fan-shaped spray pattern, so to create a water curtain over window, wall and roof against exposure fires.



- Certificate: UL Listed / FM Approved
- Standard: UL 199, NFPA 13
- Feature: K1.4 to K11.2, outside
- W. pressure: 175 psi
- O. pressure: Min 7 psi
- Surface: Rough brass / chrome plated



Main parts and material

Body	Brass	Heat responsive element	/
Frame	/	Sealing assembly	/

Available size

Type	Nominal K-Factor	Response type	Orifice	Connection	Working pressure (psi)	Ref. No.
Open nozzle	K1.4 (K20)	/	1/4"	1/2", NPT or BSPT	175	S8901 (UL/FM)
Open nozzle	K1.9 (K27)	/	5/16"	1/2", NPT or BSPT	175	S8902 (UL/FM)
Open nozzle	K2.8 (K40)	/	3/8"	1/2", NPT or BSPT	175	S8903 (UL/FM)
Open nozzle	K4.2 (K60)	/	7/16"	1/2", NPT or BSPT	175	S8904 (UL/FM)
Open nozzle	K5.6 (K80)	/	1/2"	1/2", NPT or BSPT	175	S8905 (UL)
Open nozzle	K8.0 (K115)	/	17/32"	3/4", NPT or BSPT	175	S8906 (UL)
Open nozzle	K11.2 (K161)	/	5/8"	3/4", NPT or BSPT	175	S8907 (UL)