


Malleable iron reducing coupling (Reducing socket / Reducer)



- Certificate: UL Listed / FM Approved
- Standard: ASME B16.3
- Material: Malleable iron ASTM A197
- Thread: NPT
- W. pressure: Class 150, 300 psi (-29°C to 66°C)
Class 300, 1000 / 1500 / 2000 psi (-29°C to 66°C)
- Surface: Black iron / hot dip galvanized



Available size (Class 150)

Inch	Size		A mm	Ref. No.
	DN	mm		
1/2" x 1/4"	15 x 8	21.3 x 13.7	31.8	M7405 (UL)
1/2" x 3/8"	15 x 10	21.3 x 17.1	31.8	M7406 (UL/FM)
3/4" x 1/4"	20 x 8	26.7 x 13.7	36.6	M7408 (UL)
3/4" x 3/8"	20 x 10	26.7 x 17.1	36.6	M7409 (UL/FM)
1" x 3/8"	25 x 10	33.4 x 17.1	42.9	M7412 (UL/FM)
1" x 1/2"	25 x 15	33.4 x 21.3	42.9	M7413 (UL/FM)
1" x 3/4"	25 x 20	33.4 x 26.7	42.9	M7414 (UL/FM)
1-1/4" x 1/2"	32 x 15	42.2 x 21.3	52.3	M7416 (UL/FM)
1-1/4" x 3/4"	32 x 20	42.2 x 26.7	52.3	M7417 (UL/FM)
1-1/4" x 1"	32 x 25	42.2 x 33.4	52.3	M7418 (UL/FM)
1-1/2" x 1/2"	40 x 15	48.3 x 21.3	58.7	M7421 (UL/FM)
1-1/2" x 3/4"	40 x 20	48.3 x 26.7	58.7	M7422 (UL/FM)
1-1/2" x 1"	40 x 25	48.3 x 33.4	58.7	M7423 (UL/FM)
1-1/2" x 1-1/4"	40 x 32	48.3 x 42.2	58.7	M7424 (UL/FM)
2" x 1/2"	50 x 15	60.3 x 21.3	71.4	M7425 (UL/FM)

Malleable iron reducing coupling (Reducing socket / Reducer)

Available size (Class 150)

Size			A	Ref. No.
Inch	DN	mm	mm	
2" x 3/4"	50 x 20	60.3 x 26.7	71.4	M7427 (UL/FM)
2" x 1"	50 x 25	60.3 x 33.4	71.4	M7429 (UL/FM)
2" x 1-1/4"	50 x 32	60.3 x 42.2	71.4	M7430 (UL/FM)
2" x 1-1/2"	50 x 40	60.3 x 48.3	71.4	M7431 (UL/FM)
2-1/2" x 1-1/2"	65 x 40	73.0 x 48.3	82.6	M7436 (UL/FM)
2-1/2" x 2"	65 x 50	73.0 x 60.3	82.6	M7437 (UL/FM)
3" x 1-1/2"	80 x 40	88.9 x 48.3	93.7	M7443 (UL/FM)
3" x 2"	80 x 50	88.9 x 60.3	93.7	M7444 (UL/FM)
3" x 2-1/2"	80 x 65	88.9 x 73.0	93.7	M7445 (UL/FM)
4" x 2"	100 x 50	114.3 x 60.3	111.3	M7451 (UL/FM)
4" x 3"	100 x 80	114.3 x 88.9	111.3	M7453 (UL/FM)

Available size (Class 300)

Size			A	Ref. No.
Inch	DN	mm	mm	
3/8" x 1/4"	10 x 8	17.1 x 13.7	36.6	M7403-300 (ISO)
1/2" x 1/4"	15 x 8	21.3 x 13.7	42.9	M7405-300 (ISO)
1/2" x 3/8"	15 x 10	21.3 x 17.1	42.9	M7406-300 (ISO)
3/4" x 1/4"	20 x 8	26.7 x 13.7	44.5	M7408-300 (ISO)
3/4" x 3/8"	20 x 10	26.7 x 17.1	44.5	M7409-300 (ISO)
3/4" x 1/2"	20 x 15	26.7 x 21.3	44.5	M7410-300 (ISO)
1" x 3/8"	25 x 10	33.4 x 17.1	50.8	M7412-300 (ISO)
1" x 1/2"	25 x 15	33.4 x 21.3	50.8	M7413-300 (ISO)
1" x 3/4"	25 x 20	33.4 x 26.7	50.8	M7414-300 (ISO)
1-1/4" x 1/2"	32 x 15	42.2 x 21.3	60.5	M7416-300 (ISO)
1-1/4" x 3/4"	32 x 20	42.2 x 26.7	60.5	M7417-300 (ISO)
1-1/4" x 1"	32 x 25	42.2 x 33.4	60.5	M7418-300 (ISO)
1-1/2" x 1/2"	40 x 15	48.3 x 21.3	68.3	M7421-300 (ISO)
1-1/2" x 3/4"	40 x 20	48.3 x 26.7	68.3	M7422-300 (ISO)
1-1/2" x 1"	40 x 25	48.3 x 33.4	68.3	M7423-300 (ISO)

Malleable iron reducing coupling (Reducing socket / Reducer)

Available size (Class 300)

Inch	Size		A	Ref. No.
	DN	mm	mm	
1-1/2" x 1-1/4"	40 x 32	48.3 x 42.2	68.3	M7424-300 (ISO)
2" x 1/2"	50 x 15	60.3 x 21.3	81.0	M7425-300 (ISO)
2" x 3/4"	50 x 20	60.3 x 26.7	81.0	M7427-300 (ISO)
2" x 1"	50 x 25	60.3 x 33.4	81.0	M7429-300 (ISO)
2" x 1-1/4"	50 x 32	60.3 x 42.2	81.0	M7430-300 (ISO)
2" x 1-1/2"	50 x 40	60.3 x 48.3	81.0	M7431-300 (ISO)
2-1/2" x 1-1/2"	65 x 40	73.0 x 48.3	81.0	M7436-300 (ISO)
2-1/2" x 2"	65 x 50	73.0 x 60.3	93.7	M7437-300 (ISO)
3" x 2"	80 x 50	88.9 x 60.3	103.1	M7444-300 (ISO)
3" x 2-1/2"	80 x 65	88.9 x 73.0	103.1	M7445-300 (ISO)
4" x 3"	100 x 80	114.3 x 88.9	110.0	M7453-300 (ISO)