


Malleable iron hexagon head bushing (Outside head)



- Certificate: UL Listed / FM Approved
- Standard: ASME B16.14
- Material: Malleable iron ASTM A197
- Thread: NPT
- W. pressure: Class 150, 300 psi (-29°C to 66°C)
- Surface: Black iron / hot dip galvanized



Available size (Class 150)

Inch	Size		A (Min)	Ref. No.
	DN	mm	mm	
1/2" x 1/8"	15 x 6	21.3 x 10.3	19.0	M7804 (UL)
1/2" x 1/4"	15 x 8	21.3 x 13.7	19.0	M7805 (UL/FM)
1/2" x 3/8"	15 x 10	21.3 x 17.1	19.0	M7806 (UL/FM)
3/4" x 1/8"	20 x 6	26.7 x 10.2	21.6	M7807 (UL)
3/4" x 1/4"	20 x 8	26.7 x 13.7	21.6	M7808 (UL)
3/4" x 3/8"	20 x 10	26.7 x 17.1	21.6	M7809 (UL/FM)
3/4" x 1/2"	20 x 15	26.7 x 21.3	21.6	M7810 (UL/FM)
1" x 1/2"	25 x 15	33.4 x 21.3	25.5	M7813 (UL/FM)
1" x 3/4"	25 x 20	33.4 x 26.7	25.5	M7814 (UL/FM)
1-1/4" x 3/4"	32 x 20	42.2 x 26.7	27.4	M7817 (UL/FM)
1-1/4" x 1"	32 x 25	42.2 x 33.4	27.4	M7818 (UL/FM)
1-1/2" x 1"	40 x 25	48.3 x 33.4	29.0	M7823 (UL/FM)
1-1/2" x 1-1/4"	40 x 32	48.3 x 42.2	29.0	M7824 (UL/FM)
2" x 1-1/4"	50 x 32	60.3 x 42.2	31.0	M7830 (UL/FM)
2" x 1-1/2"	50 x 40	60.3 x 48.3	31.0	M7831 (UL/FM)

Malleable iron hexagon head bushing (Outside head)

Available size (Class 150)

Inch	Size		A (Min)	Ref. No.
	DN	mm	mm	
2-1/2" x 1-1/2"	65 x 40	73.0 x 48.3	36.6	M7836 (UL/FM)
2-1/2" x 2"	65 x 50	73.0 x 60.3	36.6	M7837 (UL/FM)
3" x 2"	80 x 50	88.9 x 60.3	40.9	M7844 (UL/FM)
3" x 2-1/2"	80 x 65	88.9 x 73.0	40.9	M7845 (UL/FM)
4" x 3"	100 x 80	114.3 x 88.9	43.7	M7853 (UL/FM)