



Inlet stop valve

- Certificate: LPCB Approved
- Standard: BS 5154
- Material: Copper alloy
- Function: For hose reel and hydrant system
- Surface: Rough brass / red coating

Available size

Size	Type	Pressure gauge	Inlet	Outlet	Working pressure (bar)	Ref. No.
DN 25	Gate valve, handwheel	No	1" BSP, F	1" BSP, F	16 / 20	FE6801
DN 25	Gate valve, lockshield (Key)	No	1" BSP, F	1" BSP, F	16 / 20	FE6802
DN 25	Ball valve	No	1" BSP, F	1" BSP, F	16 / 20	FE6803
DN 25	Ball valve	Yes	1" BSP, F	1" BSP, F	16 / 20	FE6804
DN 25	Angle valve, handwheel	Yes	1" BSP, F	1" BSP, M	16 / 20	FE6805



Pressure reducing valve

- Certificate: ISO
- Standard: Refer to BS EN 671-1
- Material: Copper alloy
- Function: Reduce the inlet pressure of hose reel
- Surface: Chromed brass

Available size

Size	Inlet	Outlet	Max inlet pressure	Outlet pressure regulation	Working pressure (bar)	Ref. No.
DN 25	1" BSP, F	1" BSP, F	20 bar	1 ~ 4 bar	25	FE6901
DN 40	1.5" BSP, F	1.5" BSP, F	20 bar	1 ~ 4 bar	25	FE6902
DN 50	2" BSP, F	2" BSP, F	20 bar	1 ~ 4 bar	25	FE6903