

Horizontal two compartment fire cabinet

Horizontal fire cabinet has dual compartment for protecting both hose reel and layflat fire hose (or extinguisher). The cabinet is surface or recess mounted in a wall, with compact design for saving space and easy access for operation.






Certificate: ISO
Standard: Refe

· Stanuaru.


Mounting:

- Refer to BS 5041
- Capacity: Fire hose reel + extinguisher
 - Layflat hose with branchpipe
 - Wall surface / recessed
- Surface: Red powder coating / bright SS



FΜ

LPCB



VdS E

Main parts and material

	Box / door	Cold rolled steel or SS, 1.0 / 1.2 / 1.5 mm thickness	Door type	Double doors, from left and right open 180°, bullet hinge or continuous piano hinge	
0	Door glazing	Non (full solid), or acrylic viewing panel, slotted inside the door or embedded into the door with rubber raised edge	Lock	Rotary pull lock, or keyed cylinder lock	

Available size

Content	Capacity	Mounting	Dimension W x H x D (mm)	Ref. No.
Swinging arm hose reel + dry powder extinguisher	19mm x 30m + 1 x 6 kg	Surface / recessed	1050 x 800 x 250	FE9601
Swinging arm hose reel + dry powder extinguisher	25mm x 30m + 1 x 6 kg	Surface / recessed	1050 x 800 x 270	FE9602
Layflat hose with branchpipe	2.5" x 30m, 2 sets	Surface / recessed	1163 x 560 x 300	FE9603

Note:

1. For recessed type, it contains projection trim on the external face of cabinet with width 38mm.

2. Cabinet can be LPCB approved if it contains LPCB approved fire hose reel.

