


Vertical two compartment fire cabinet

Vertical fire cabinet has dual compartment for protecting both hose reel and layflat fire hose (or extinguisher). The cabinet is surface or recess mounted, with compact design for saving space and easy access for operation.









· Standard: Refer to BS 5041


· Capacity: Fire hose reel + layflat hose


Fire hose reel + extinguisher


Mounting: Wall surface / recessed

· Surface: Red powder coating / bright SS









Main parts and material

| Box / door | Cold rolled steel or SS, 1.0 / 1.2 / 1.5 mm thickness | Door type | Double doors, from left and right open 180°, bullet hinge or continuous piano hinge |
|--------------|---|-----------|---|
| Door glazing | Non (full solid), or acrylic viewing panel, slotted inside the door or embedded into the door with rubber raised edge | Lock | Rotary pull lock, or keyed cylinder lock |

Available size

| Content | Capacity | Mounting | Dimension W x H x D (mm) | Ref. No. |
|---|---------------------------------------|--------------------|-----------------------------|----------|
| Swinging arm hose reel + dry powder extinguisher | 19mm x 30m + 3 x 6 kg | Surface / recessed | 700 x 1400 x 250 | FE9701 |
| Swinging arm hose reel + dry powder extinguisher | 25mm x 30m + 3 x 6 kg | Surface / recessed | 700 x 1400 x 270 | FE9702 |
| Swinging arm hose reel + landing valve & layflat hose with branchpipe | 25mm x 30m + 2.5" & 2.5" x 30m | Surface / recessed | 800 x 1600 x 300 | FE9703 |
| Swinging arm hose reel + DP extinguisher & layflat hose with branchpipe | 25mm x 30m + 1 x 6 kg & 2.5" x 30m | Surface / recessed | 800 x 1600 x 300 | FE9704 |

Note

- 1. For recessed type, it contains projection trim on the external face of cabinet with width 38mm.
- 2. Cabinet can be LPCB approved if it contains LPCB approved fire hose reel.











