


Malleable cast iron plain plug



- Certificate: UL Listed / FM Approved / NSF 61
- Standard: ISO 49 / EN 10242, symbol C
- Material: BS EN 1562, EN-GJMB-350-10
- Thread: BSPT
- W. pressure: 20 ~ 25 bar, ≤ PN25
- Surface: Black iron / hot dip galvanized



Available size

Inch	Size		A (min)	Ref. No.
	DN	mm	mm	
1/4"	8	13.5	14	M3501 (UL/FM)
3/8"	10	17.2	15	M3502 (UL/FM)
1/2"	15	21.3	18	M3503 (UL/FM)
3/4"	20	26.9	20	M3504 (UL/FM)
1"	25	33.7	23	M3505 (UL/FM)
1-1/4"	32	42.4	29	M3506 (UL/FM)
1-1/2"	40	48.3	30	M3507 (UL/FM)
2"	50	60.3	36	M3508 (UL/FM)
2-1/2"	65	76.1	39	M3509 (UL/FM)
3"	80	88.9	44	M3510 (UL/FM)
4"	100	114.3	58	M3511 (UL/FM)
6"	150	165.1	71.5	M3513 (UL/FM)

Note: NSF 61 certificate is available for M3501 ~ M3511, except M3513.