


## Malleable iron cap (Recessed)



- Certificate: UL Listed / FM Approved
- Standard: ASME B16.3
- Material: Malleable iron ASTM A197
- Thread: NPT
- W. pressure: Class 150, 300 psi (-29°C to 66°C)  
Class 300, 1000 / 1500 / 2000 psi (-29°C to 66°C)
- Surface: Black iron / hot dip galvanized



### Available size (Class 150)

Inch	Size		A (Min)	Ref. No.
	DN	mm	mm	
1/2"	15	21.3	22.1	M8403 (UL/FM)
3/4"	20	26.7	24.6	M8404 (UL/FM)
1"	25	33.4	29.5	M8405 (UL/FM)
1-1/4"	32	42.2	32.5	M8406 (UL/FM)
1-1/2"	40	48.3	33.8	M8407 (UL/FM)
2"	50	60.3	36.8	M8408 (UL/FM)
2-1/2"	65	73.0	43.2	M8409 (UL/FM)
3"	80	88.9	45.7	M8410 (UL/FM)
4"	100	114.3	52.8	M8411 (UL/FM)
5"	125	141.3	58.9	M8412 (UL/FM)
6"	150	168.3	64.8	M8413 (UL/FM)

## Malleable iron cap (Recessed)

### Available size (Class 300)

Inch	Size		A	Ref. No.
	DN	mm	mm	
1/4"	8	13.7	19.8	M8401-300 (ISO)
3/8"	10	17.1	21.1	M8402-300 (ISO)
1/2"	15	21.3	24.9	M8403-300 (ISO)
3/4"	20	26.7	27.4	M8404-300 (ISO)
1"	25	33.4	32.0	M8405-300 (ISO)
1-1/4"	32	42.2	35.1	M8406-300 (ISO)
1-1/2"	40	48.3	36.3	M8407-300 (ISO)
2"	50	60.3	42.7	M8408-300 (ISO)
2-1/2"	65	73.0	52.3	M8409-300 (ISO)
3"	80	88.9	55.1	M8410-300 (ISO)
4"	100	114.3	60.5	M8411-300 (ISO)