


Brass Y type strainer



- Certificate: ISO
- Material: Brass
- Connection: Thread, BSPT / NPT
- Screen: Standard 18 or 12 mesh
- Temperature: 0°C to 150°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass

Available size

Size		L (mm)	Mesh screen	Connection	Working pressure	Ref. No.
Inch	DN					
1/2"	15	70	18	BSPT / NPT	PN 16	VC1501
3/4"	20	84	18	BSPT / NPT	PN 16	VC1502
1"	25	100	18	BSPT / NPT	PN 16	VC1503
1-1/4"	32	117	18	BSPT / NPT	PN 16	VC1504
1-1/2"	40	137	18	BSPT / NPT	PN 16	VC1505
2"	50	170	18	BSPT / NPT	PN 16	VC1506
2-1/2"	65	205	12	BSPT / NPT	PN 16	VC1507
3"	80	220	12	BSPT / NPT	PN 16	VC1508
4"	100	265	12	BSPT / NPT	PN 16	VC1509

Brass foot valve with strainer



- Certificate: ISO
- Material: Brass
- Connection: Thread, BSPP
- Screen: SS or brass
- Temperature: -20°C to 120°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass

Available size

Size		Dimension (mm)		Connection	Working pressure	Ref. No.
Inch	DN	A	D			
1/2"	15	66	33	BSPP	PN 16	VC1601
3/4"	20	78	40	BSPP	PN 16	VC1602
1"	25	88	46	BSPP	PN 16	VC1603
1-1/4"	32	103	58	BSPP	PN 16	VC1604
1-1/2"	40	112	67	BSPP	PN 16	VC1605
2"	50	134	80	BSPP	PN 16	VC1606

VC15-16 /