

## Stainless steel screwed swing check valve



- Certificate: ISO
- Material: SS304 / SS316
- Connection: Thread, BSPT / BSPP / NPT
- Temperature: -20°C to 180°C
- W. pressure: 200 psi
- Surface: Sandblasted

### Available size

Size		Dimension (mm)		Connection	Working pressure (psi)	Ref. No.
Inch	DN	L	H			
1/2"	15	50	35	BSPT / BSPP / NPT	200	VC6301
3/4"	20	60	40	BSPT / BSPP / NPT	200	VC6302
1"	25	74	47	BSPT / BSPP / NPT	200	VC6303
1-1/4"	32	84	53	BSPT / BSPP / NPT	200	VC6304
1-1/2"	40	94	60	BSPT / BSPP / NPT	200	VC6305
2"	50	114	70	BSPT / BSPP / NPT	200	VC6306
2-1/2"	65	146	86	BSPT / BSPP / NPT	200	VC6307
3"	80	165	102	BSPT / BSPP / NPT	200	VC6308
4"	100	192	122	BSPT / BSPP / NPT	200	VC6309

## Stainless steel screwed spring check valve



- Certificate: ISO
- Material: SS304 / SS316
- Connection: Thread, BSPT / BSPP / NPT
- Temperature: -20°C to 180°C
- W. pressure: 200 psi
- Surface: Sandblasted

### Available size

Size		L (mm)	Connection	Working pressure (psi)	Ref. No.
Inch	DN				
1/2"	15	59	BSPT / BSPP / NPT	200	VC6401
3/4"	20	67	BSPT / BSPP / NPT	200	VC6402
1"	25	74	BSPT / BSPP / NPT	200	VC6403
1-1/4"	32	86	BSPT / BSPP / NPT	200	VC6404
1-1/2"	40	93	BSPT / BSPP / NPT	200	VC6405
2"	50	108	BSPT / BSPP / NPT	200	VC6406
2-1/2"	65	115	BSPT / BSPP / NPT	200	VC6407
3"	80	128	BSPT / BSPP / NPT	200	VC6408
4"	100	151	BSPT / BSPP / NPT	200	VC6409