


## PVC coated FMC

PVC coated FMC (Flexible metal conduit) has a spiral shape that allows it to bend easily, withstand impact and crushing force. Both Halogen free type and standard type are available.



- Certificate: ISO
- Standard: Refer to UL 1
- Material: Galv. carbon steel + PVC jacket
- IP rating: IP 40
- Color: Black, grey, or customized



### Available size

Trade size	Metric designator	Outer diameter (mm)	Inner diameter (mm)	Min bend radius (mm)	Coil length (m)	Ref. No.
3/8"	12	17.0	12.0	50	100 / 50 / 30	C2021
1/2"	16	21.0	16.0	75	100 / 50 / 30	C2022
3/4"	21	26.0	20.0	100	100 / 50 / 30	C2023
1"	27	32.0	25.0	125	100 / 50 / 30	C2024
1-1/4"	35	40.0	32.0	160	50 / 25 / 20	C2025
1-1/2"	41	47.0	38.0	190	50 / 25 / 15	C2026
2"	53	61.0	51.0	255	50 / 15 / 10	C2027
2-1/2"	63	72.0	63.0	320	20 / 15 / 10	C2028
3"	78	88.0	75.0	380	20 / 15 / 10	C2029
4"	103	114.0	100.0	510	20 / 15 / 10	C2030