

Rectangular junction box (Handy box)



- Certificate: UL Listed
- Standard: UL 514A / CSA C22.2 No. 18.1
- Material: Carbon steel, drawn
- Surface: Zinc coating
- Application: Protect electrical wiring and switch

Available size

Size	Deep	Knockout (KO)		Thickness (mm)	Ref. No.
		Side	Bottom		
4" x 2"	1-7/8"	8 x 1/2"	3 x 1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	C3601
4" x 2"	1-7/8"	6 x 3/4"	2 x 3/4"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	C3602
4" x 2"	1-7/8"	4 x 1/2", 4 x 3/4"	2 x 1/2", 1 x 3/4"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	C3603
4" x 2"	2-1/8"	8 x 1/2"	3 x 1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	C3604
4" x 2"	2-1/8"	6 x 3/4"	2 x 3/4"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	C3605
4" x 2"	2-1/8"	4 x 1/2", 4 x 3/4"	2 x 1/2", 1 x 3/4"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	C3606
4" x 2"	2-1/8"	6 x 1"	2 x 1/2", 1 x 3/4"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	C3607

Rectangular box cover



- Certificate: UL Listed
- Standard: UL 514A / CSA C26.2 No. 18.1-13
- Material: Carbon steel, drawn
- Surface: Zinc coating
- Application: To cover rectangular box

Available size

Size	Description	Thickness (mm)	Ref. No.
4" x 2"	Blank (None KO)	0.8 / 1.0 / 1.2 / 1.5	C3611
4" x 2"	1/2" KO	0.8 / 1.0 / 1.2 / 1.5	C3612
4" x 2"	1-19/32", for 4-wire twist-lock single flush receptacle	0.8 / 1.0 / 1.2 / 1.5	C3613
4" x 2"	1-13/32", for single receptacle	0.8 / 1.0 / 1.2 / 1.5	C3614
4" x 2"	For duplex flush receptacle	0.8 / 1.0 / 1.2 / 1.5	C3615
4" x 2"	With 15/32" bushed hole	0.8 / 1.0 / 1.2 / 1.5	C3616
4" x 2"	For single GFCI receptacle	0.8 / 1.0 / 1.2 / 1.5	C3617
4" x 2"	For single toggle switch	0.8 / 1.0 / 1.2 / 1.5	C3618