

## CE surface emergency exit sign



- Certificate: CE / TUV approved
- Standard: IEC 60598-2-22, BS 5499
- Material: Aluminum housing, acrylic panel
- Feature: Automatic self-diagnosis, IP20
- Temperature: -10°C to 55°C
- Mounting: Surface, wall or ceiling



### Available size

Color	Configuration	Pictograms	Light source	Power	AC voltage	Backup battery	Ref. No.
Green	Single face	Running man + arrow	LED	3W	220V - 240V	≥ 180 min	C8101
Green	Single face	EXIT	LED	3W	220V - 240V	≥ 180 min	C8102
Green	Single face	Running man + arrow + EXIT	LED	3W	220V - 240V	≥ 180 min	C8103

## CE hanging emergency exit sign



- Certificate: CE / TUV approved
- Standard: IEC 60598-2-22, BS 5499
- Material: Aluminum housing, acrylic panel
- Feature: IP20
- Temperature: -10°C to 55°C
- Mounting: Suspended



### Available size

Color	Configuration	Pictograms	Light source	Power	AC voltage	Backup battery	Ref. No.
Green	Double face	Running man + arrow	LED	2W	220V - 240V	≥ 180 min	C8201
Green	Double face	EXIT	LED	2W	220V - 240V	≥ 180 min	C8202
Green	Double face	Image + text	LED	2W	220V - 240V	≥ 180 min	C8203