


Lever operated hand-held branchpipe

Branchpipe connects to water supply via a fire hose and is used to project water for fire service use. For hand-held branchpipe, it is smooth bore, lever operated to control flow pattern to full jet, spray jet or shut.



- Certificate: LPCB Approved
- Standard: EN 15182-3
- Spray angle: 15° ~ 27°
- Throw at 6 bar: 30m at full jet, 15m at spray jet
- Flow at 6 bar: 230LPM at full jet, 220LPM at full cone
- Hydraulic test: 22.5 bar
- Surface: Black or red plastic



Main parts and material

Body / nozzle	Aluminum alloy, BS 1459 LM25	Body shaft gripping device	Rubber covered aluminum
Inlet	Aluminum alloy, BS 336 instantaneous	Open and shut-off device	Aluminum alloy, lever with ball valve control

Available size

Size	Barrel material	Inlet	Nozzle size (mm)	Normal pressure (bar)	Ref. No.
2.5"	AL, black coating	BS336, M	13	16	FE3501
2.5"	Rubber, red	BS336, M	13	16	FE3502
2"	AL, black coating	BSP, M	13	16	FE3503
2"	Rubber, red	BSP, M	13	16	FE3504
2.5"	AL, black coating	BSP, M	16	16	FE3505
2.5"	Rubber, red	BSP, M	16	16	FE3506