


Malleable iron 45° straight elbow



- Certificate: UL Listed / FM Approved
- Standard: ASME B16.3
- Material: Malleable iron ASTM A197
- Thread: NPT
- W. pressure: Class 150, 300 psi (-29°C to 66°C)
Class 300, 1000 / 1500 / 2000 psi (-29°C to 66°C)
- Surface: Black iron / hot dip galvanized



Available size (Class 150)

Inch	Size		A	Ref. No.
	DN	mm	mm	
1/2"	15	21.3	22.4	M5503 (UL/FM)
3/4"	20	26.7	24.9	M5504 (UL/FM)
1"	25	33.4	28.5	M5505 (UL/FM)
1-1/4"	32	42.4	32.8	M5506 (UL/FM)
1-1/2"	40	48.3	36.3	M5507 (UL/FM)
2"	50	60.3	42.7	M5508 (UL/FM)
2-1/2"	65	73.0	49.5	M5509 (UL/FM)
3"	80	88.9	55.1	M5510 (UL/FM)
4"	100	114.3	66.3	M5511 (UL/FM)
6"	150	168.3	87.9	M5513 (UL/FM)

Malleable iron 45° straight elbow

Available size (Class 300)

Inch	Size		A	Ref. No.
	DN	mm	mm	
1/4"	8	13.7	20.6	M5501-300 (ISO)
3/8"	10	17.1	22.4	M5502-300 (ISO)
1/2"	15	21.3	25.4	M5503-300 (ISO)
3/4"	20	26.7	28.7	M5504-300 (ISO)
1"	25	33.4	33.3	M5505-300 (ISO)
1-1/4"	32	42.2	38.1	M5506-300 (ISO)
1-1/2"	40	48.3	42.9	M5507-300 (ISO)
2"	50	60.3	50.8	M5508-300 (ISO)
2-1/2"	65	73.0	57.2	M5509-300 (ISO)
3"	80	88.9	63.5	M5510-300 (ISO)
4"	100	114.3	71.0	M5511-300 (ISO)