





· Certificate: ISO

· Standard: Refer to NFPA 11, UL 162, GB 50151

· Material: Aluminum body, rubber handle and bumper,

with SS304 pick-up tube

· Feature: Straight jet, wide spray

· W. pressure: 200 psi

· Surface: Hard anodized

## Available size

Flow @ 100 psi (gpm)	Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
106	AL	1-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2401 (ISO)
106	AL	2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2402 (ISO)
106	AL	2-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2403 (ISO)





## Self-inducting foam nozzle (Pistol grip and foam concentrate can)

· Certificate: ISO

· Standard: Refer to NFPA 11, UL 162, GB 50151

· Material: Aluminum body, rubber handle and bumper,

with 2.0L foam concentrate can

· Feature: Self-contained, straight jet, wide spray

· W. pressure: 200 psi

· Surface: Hard anodized

## Available size

Flow @ 100 psi (gpm)	Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
20	AL	1-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2501 (ISO)
20	AL	2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2502 (ISO)
20	AL	2-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2503 (ISO)











