



Self-inducting foam nozzle (Pistol grip)

 Certificate: 	ISO
Standard:	Refer to NFPA 11, UL 162, GB 50151
Material:	Aluminum body, rubber handle and bumper,
	with SS304 pick-up tube
· Feature:	Straight jet, wide spray
• W. pressure:	200 psi
Surface:	Hard anodized

Available size

Flow @ 100 psi (gpm)	Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
106	AL	1-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2401 (ISO)
106	AL	2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2402 (ISO)
106	AL	2-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2403 (ISO)



Self-inducting foam nozzle (Pistol grip and foam concentrate can)

ISO
Refer to NFPA 11, UL 162, GB 50151
Aluminum body, rubber handle and bumper,
with 2.0L foam concentrate can
Self-contained, straight jet, wide spray
200 psi
Hard anodized

Available size

Flow @ 100 psi (gpm)	Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
20	AL	1-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2501 (ISO)
20	AL	2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2502 (ISO)
20	AL	2-1/2" BS336 / Storz / NH	Quick connection	0.5% ~ 6%	B2503 (ISO)

ΰU

B24-25/

