


Manual operated wheel control foam monitor (500 to 1250 GPM)

Manual operated wheel control foam monitor is designed with large clear waterway to deliver a powerful and far-reaching foam stream. It is mounted in fixed installation or on vehicle for one man operation.



- Certificate: UL Listed
- Standard: NFPA 11, UL 162, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Double handwheel control, straight jet, wide spray
- Rotation: 360° horizontal
- Elevation: 90° above + 65° below
- W. pressure: 175 psi
- Surface: Red FBE coating



Main parts and material

Construction	SS304 or SS316	Pre-assembly nozzle	SS304 or SS316, with pick-up tube
Control	Double handwheel with worm gear, carbon steel	Other components	Double-row SS ball bearing in swivel joint, pressure gauge as option

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Foam concentrate	Ref. No.
GPM	LPM						
500	1900	SS	4" or 6" FLG	4" BSP, M	Self-inducting	AFFF 3%	B3801 (UL)
750	2850	SS	4" or 6" FLG	4" BSP, M	Self-inducting	AFFF 3%	B3802 (UL)
1000	3800	SS	4" or 6" FLG	4" BSP, M	Self-inducting	AFFF 3%	B3803 (UL)
1250	4750	SS	4" or 6" FLG	4" BSP, M	Self-inducting	AFFF 3%	B3804 (UL)
500, 750, 1000	1900, 2850, 3800	SS	4" or 6" FLG	4" BSP, M	Self-inducting	AFFF 3%	B3805 (UL)*

Note: *The outlet is also available with JRCP type (Jet ratio controller with pick-up tube).