


Manual operated lever control foam monitor (Double waterway & air-aspirating nozzle)

Manual operated lever control foam monitor (Double waterway & air-aspirating nozzle) is designed with large clear waterway to deliver a powerful and far-reaching foam stream. It is mounted in fixed installation or on vehicle.



- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Lever control, double waterway, straight jet
- Rotation: 360° horizontal
- Elevation: 85° above + 45° below
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE



Main parts and material

Construction	Aluminum alloy	Pre-assembly nozzle	Aluminum alloy, with pick-up tube for self-inducting type
Control	Hand lever or tiller, carbon steel	Other components	Double-row SS ball bearing in swivel joint, twist lock, pressure gauge

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Foam concentrate	Ref. No.
GPM	LPM						
379	1440	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4101 (ISO)
505	1920	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4102 (ISO)
632	2400	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4103 (ISO)
758	2880	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4104 (ISO)
379	1440	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4105 (ISO)
505	1920	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4106 (ISO)
632	2400	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4107 (ISO)
758	2880	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4108 (ISO)