


## Manual operated lever control foam monitor (Air-aspirating nozzle)

Manual operated lever control foam monitor (Air-aspirating nozzle) is designed with large clear waterway to deliver a powerful and far-reaching foam stream. It is mounted in fixed installation or on vehicle.



- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Lever control, straight jet
- Rotation: 360° horizontal
- Elevation: 75° above + 45° below
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE



### Main parts and material

|                     |                                    |                            |  |
|---------------------|------------------------------------|----------------------------|--|
| <b>Construction</b> | Aluminum alloy                     | <b>Pre-assembly nozzle</b> | Aluminum alloy, with pick-up tube for self-inducting type              |
| <b>Control</b>      | Hand lever or tiller, carbon steel | <b>Other components</b>    | Double-row SS ball bearing in swivel joint, twist lock, pressure gauge |

### Available size

| Flow @ 100 psi (7 bar) |      | Material | Base inlet   | Outlet for nozzle | Nozzle type        | Foam concentrate | Ref. No.    |
|------------------------|------|----------|--------------|-------------------|--------------------|------------------|-------------|
| GPM                    | LPM  |          |              |                   |                    |                  |             |
| 379                    | 1440 | AL       | 3" or 4" FLG | 2-1/2" NH         | Self-inducting     | 0.5% ~ 6%        | B4201 (ISO) |
| 505                    | 1920 | AL       | 3" or 4" FLG | 2-1/2" NH         | Self-inducting     | 0.5% ~ 6%        | B4202 (ISO) |
| 632                    | 2400 | AL       | 3" or 4" FLG | 2-1/2" NH         | Self-inducting     | 0.5% ~ 6%        | B4203 (ISO) |
| 758                    | 2880 | AL       | 3" or 4" FLG | 2-1/2" NH         | Self-inducting     | 0.5% ~ 6%        | B4204 (ISO) |
| 1011                   | 3840 | AL       | 3" or 4" FLG | 3-1/2" NH         | Self-inducting     | 0.5% ~ 6%        | B4205 (ISO) |
| 1263                   | 4800 | AL       | 3" or 4" FLG | 3-1/2" NH         | Self-inducting     | 0.5% ~ 6%        | B4206 (ISO) |
| 379                    | 1440 | AL       | 3" or 4" FLG | 2-1/2" NH         | Non self-inducting | 0.5% ~ 6%        | B4207 (ISO) |
| 505                    | 1920 | AL       | 3" or 4" FLG | 2-1/2" NH         | Non self-inducting | 0.5% ~ 6%        | B4208 (ISO) |

## Manual operated lever control foam monitor (Air-aspirating nozzle)

### Available size

| Flow @ 100 psi (7 bar) |      | Material | Base inlet   | Outlet for nozzle | Nozzle type        | Foam concentrate | Ref. No.    |
|------------------------|------|----------|--------------|-------------------|--------------------|------------------|-------------|
| GPM                    | LPM  |          |              |                   |                    |                  |             |
| 632                    | 2400 | AL       | 3" or 4" FLG | 2-1/2" NH         | Non self-inducting | 0.5% ~ 6%        | B4209 (ISO) |
| 758                    | 2880 | AL       | 3" or 4" FLG | 2-1/2" NH         | Non self-inducting | 0.5% ~ 6%        | B4210 (ISO) |
| 1011                   | 3840 | AL       | 3" or 4" FLG | 3-1/2" NH         | Non self-inducting | 0.5% ~ 6%        | B4211 (ISO) |
| 1263                   | 4800 | AL       | 3" or 4" FLG | 3-1/2" NH         | Non self-inducting | 0.5% ~ 6%        | B4212 (ISO) |