

# Manual operated wheel control foam monitor (Double waterway & air-aspirating nozzle)

Manual operated wheel control foam monitor (Double waterway & air-aspirating nozzle) is designed with large clear waterway to deliver a powerful and far-reaching foam stream. It is mounted in fixed installation or on vehicle.



- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Double handwheel control, double waterway, straight jet
- Rotation: 360° horizontal
- Elevation: 90° above + 45° below
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE



## Main parts and material

<b>Construction</b>	Aluminum alloy	<b>Pre-assembly nozzle</b>	Aluminum alloy, with pick-up tube for self-inducting type
<b>Control</b>	Double handwheel with worm gear	<b>Other components</b>	Double-row SS ball bearing in swivel joint, pressure gauge

## Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Foam concentrate	Ref. No.
GPM	LPM						
379	1440	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4601 (ISO)
505	1920	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4602 (ISO)
632	2400	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4603 (ISO)
758	2880	AL	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4604 (ISO)
379	1440	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4605 (ISO)
505	1920	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4606 (ISO)
632	2400	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4607 (ISO)
758	2880	AL	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4608 (ISO)