


# Manual operated wheel control foam monitor (Dispersion jaw air-aspirating nozzle)

Manual operated wheel control foam monitor (Dispersion jaw air-aspirating nozzle) is designed with large clear waterway to deliver a powerful and far-reaching foam stream. It is mounted in fixed installation or on vehicle.



- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Double handwheel control, straight jet, fan spray
- Rotation: 360° horizontal
- Elevation: 90° above + 45° below
- W. pressure: 200 psi
- Surface: Red FBE coating



## Main parts and material

<b>Construction</b>	SS304	<b>Pre-assembly nozzle</b>	Aluminum alloy, with pick-up tube for self-inducting type
<b>Control</b>	Double handwheel with worm gear	<b>Other components</b>	Double-row SS ball bearing in swivel joint, pressure gauge

## Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Foam concentrate	Ref. No.
GPM	LPM						
505	1920	SS304	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4801 (ISO)
758	2880	SS304	3" or 4" FLG	2-1/2" NH	Self-inducting	0.5% ~ 6%	B4802 (ISO)
1011	3840	SS304	3" or 4" FLG	3-1/2" NH	Self-inducting	0.5% ~ 6%	B4803 (ISO)
1579	6000	SS304	3" or 4" FLG	3-1/2" NH	Self-inducting	0.5% ~ 6%	B4804 (ISO)
505	1920	SS304	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4805 (ISO)
758	2880	SS304	3" or 4" FLG	2-1/2" NH	Non self-inducting	0.5% ~ 6%	B4806 (ISO)
1011	3840	SS304	3" or 4" FLG	3-1/2" NH	Non self-inducting	0.5% ~ 6%	B4807 (ISO)
1579	6000	SS304	3" or 4" FLG	3-1/2" NH	Non self-inducting	0.5% ~ 6%	B4808 (ISO)