


Electrical remote control foam monitor (Dispersion jaw air-aspirating nozzle)

Electrical remote control foam monitor (Dispersion jaw air-aspirating nozzle) utilizes remote controlled mechanism to direct foam stream towards the fire. It facilitates the effective use of personnel and lowers the potential risk of injury.



- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Connection: Flanged as ANSI Class 150, EN 1092 PN16, etc.
- Feature: Wireless, programmable automatic oscillation and stow position
- Rotation: 360° horizontal
- Elevation: 90° above + 80° below
- W. pressure: 200 psi
- Surface: Hard anodized or red FBE



Main parts and material

Construction	AL or SS304, with waterproof electric drive and control box	Pre-assembly nozzle	Aluminum alloy, remote control, with pick-up tube for self-inducting type
Control	Electrical remote control mechanism, distance up to 150 m	Power	7.5A @ 24 VDC, optional 110 ~ 230 VAC

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Foam concentrate	Ref. No.
GPM	LPM						
505	1920	AL / SS304	3" or 4" FLG	2-1/2" NH	RC self-inducting	0.5% ~ 6%	B5301 (ISO)
758	2880	AL / SS304	3" or 4" FLG	2-1/2" NH	RC self-inducting	0.5% ~ 6%	B5302 (ISO)
1011	3840	AL / SS304	3" or 4" FLG	3-1/2" NH	RC self-inducting	0.5% ~ 6%	B5303 (ISO)
1263	4800	AL	3" or 4" FLG	3-1/2" NH	RC self-inducting	0.5% ~ 6%	B5304 (ISO)
1579	6000	AL	3" or 4" FLG	3-1/2" NH	RC self-inducting	0.5% ~ 6%	B5305 (ISO)
505	1920	AL / SS304	3" or 4" FLG	2-1/2" NH	RC non self-inducting	0.5% ~ 6%	B5306 (ISO)
758	2880	AL / SS304	3" or 4" FLG	2-1/2" NH	RC non self-inducting	0.5% ~ 6%	B5307 (ISO)
1011	3840	AL / SS304	3" or 4" FLG	3-1/2" NH	RC non self-inducting	0.5% ~ 6%	B5308 (ISO)
1263	4800	AL	3" or 4" FLG	3-1/2" NH	RC non self-inducting	0.5% ~ 6%	B5309 (ISO)
1579	6000	AL	3" or 4" FLG	3-1/2" NH	RC non self-inducting	0.5% ~ 6%	B5310 (ISO)