


Portable ground foam monitor

Portable ground foam monitor is compact, lightweight for easy to carry but delivers much more foam. It is simple to set up for quick attack operation, and can be left unmanned at the fire scene to conserve manpower.



- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Connection: 2-1/2" threaded, single or dual
- Feature: Portable, compact folding leg
- Rotation: 20° each side of center
- Elevation: From 30° to 60° unmanned
- W. pressure: 200 psi
- Surface: Red FBE coating



Main parts and material

Construction	Aluminum alloy, with folding legs fitted carbide-tipped spikes	Pre-assembly nozzle	Aluminum alloy, with pick-up tube
Control	Manual	Other components	Ball shutoff, large lifting handle, anchor safety strap

Available size

Flow @ 100 psi (7 bar)		Material	Base inlet	Outlet for nozzle	Nozzle type	Foam concentrate	Ref. No.
GPM	LPM						
150	570	AL	2-1/2" THD	2-1/2" NH	Self-inducting	3%, 6%	B5601 (ISO)
225	855	AL	2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%, 6%	B5602 (ISO)
350	1330	AL	2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%, 6%	B5603 (ISO)
500	1900	AL	2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%	B5604 (ISO)
225, 350, 500	855, 1330, 1900	AL	2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%, 6%	B5605 (ISO)
150	570	AL	(2) 2-1/2" THD	2-1/2" NH	Self-inducting	3%, 6%	B5606 (ISO)
225	855	AL	(2) 2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%, 6%	B5607 (ISO)
350	1330	AL	(2) 2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%, 6%	B5608 (ISO)
500	1900	AL	(2) 2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%	B5609 (ISO)
225, 350, 500	855, 1330, 1900	AL	(2) 2-1/2" THD	2-1/2" NH	Self-inducting	1%, 3%, 6%	B5610 (ISO)