


Elbow outlet



- Certificate: ISO
- Standard: MSS SP-97, GB/T 19326
- Material: Carbon steel ASTM A234, WPB
SS ASTM A403, WP304 / WP316L
- Connection: Socket weld, threaded, butt weld
- W. pressure: Class 3000 / 6000, or equal to same seamless pipe
- Surface: Oiled / hot dip galvanized
Pickling white, etc.



Available size with SW and THD

| Branch outlet size | | | Length A (mm) | | Connection | Ref. No. |
|--------------------|-----|---------|---------------|------------|---------------|----------|
| NPS | DN | OD (mm) | Class 3000 | Class 6000 | | |
| 1/2" | 15 | 21.3 | 38 ~ 45 | 46 ~ 54 | SW, NPT, BSPT | N7601 |
| 3/4" | 20 | 26.7 | 46 ~ 51 | 54 ~ 62 | SW, NPT, BSPT | N7602 |
| 1" | 25 | 33.4 | 54 ~ 62 | 61 ~ 70 | SW, NPT, BSPT | N7603 |
| 1-1/4" | 32 | 42.2 | 61 ~ 69 | 65 ~ 75 | SW, NPT, BSPT | N7604 |
| 1-1/2" | 40 | 48.3 | 64 ~ 72 | 79 ~ 89 | SW, NPT, BSPT | N7605 |
| 2" | 50 | 60.3 | 76 ~ 84 | 90 ~ 105 | SW, NPT, BSPT | N7606 |
| 2-1/2" | 65 | 73.0 | 85 ~ 95 | / | SW, NPT, BSPT | N7607 |
| 3" | 80 | 88.9 | 97 ~ 110 | / | SW, NPT, BSPT | N7608 |
| 4" | 100 | 114.3 | 125 ~ 140 | / | SW, NPT, BSPT | N7609 |

Elbow outlet

Available size with BW

| Branch outlet size | | | Length A (mm) | | Connection | Ref. No. |
|--------------------|-----|---------|---------------|-----|------------|----------|
| NPS | DN | OD (mm) | STD | XS | | |
| 1/2" | 15 | 21.3 | 38 | 43 | BW | N7611 |
| 3/4" | 20 | 26.7 | 45 | 51 | BW | N7612 |
| 1" | 25 | 33.4 | 54 | 65 | BW | N7613 |
| 1-1/4" | 32 | 42.2 | 54 | 65 | BW | N7614 |
| 1-1/2" | 40 | 48.3 | 64 | 75 | BW | N7615 |
| 2" | 50 | 60.3 | 73 | 89 | BW | N7616 |
| 2-1/2" | 65 | 73.0 | 95 | 110 | BW | N7617 |
| 3" | 80 | 88.9 | 115 | 130 | BW | N7618 |
| 4" | 100 | 114.3 | 140 | 155 | BW | N7619 |
| 5" | 125 | 141.3 | 170 | 185 | BW | N7620 |
| 6" | 150 | 168.3 | 195 | 210 | BW | N7621 |
| 8" | 200 | 219.1 | 220 | 235 | BW | N7622 |
| 10" | 250 | 273.0 | 250 | 265 | BW | N7623 |
| 12" | 300 | 323.8 | 280 | 295 | BW | N7624 |
| 14" | 350 | 355.6 | 300 | 320 | BW | N7625 |
| 16" | 400 | 406.4 | 330 | 350 | BW | N7626 |
| 18" | 450 | 457 | 370 | 390 | BW | N7627 |
| 20" | 500 | 508 | 410 | 430 | BW | N7628 |
| 24" | 600 | 610 | 490 | 515 | BW | N7629 |