


Dual-purpose portable ground foam monitor

Dual-purpose portable ground foam monitor is suitable for use as a portable monitor or a deck gun so to meet the changing demand of the fire service. It is compact, lightweight, and simple to set up for quick attack operation.



- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Connection: Threaded, single or dual
- Feature: Portable monitor and deck gun
- Rotation: 180° horizontal
- Elevation: From 12° to 75°, inbuilt safety stop
- W. pressure: 200 psi
- Surface: Red FBE coating



Main parts and material

| | | | |
|---------------------|---|----------------------------|---|
| Construction | AL, with folding legs fitted carbide-tipped spikes, lock pin for easy break apart | Pre-assembly nozzle | Aluminum alloy, with pick-up tube |
| Control | Single handwheel with worm gear | Other components | Pressure gauge, large lifting handle, anchor safety strap, ball shutoff as option |

Available size

| Flow @ 100 psi (7 bar) | | Material | Base inlet | Outlet for nozzle | Nozzle type | Foam concentrate | Ref. No. |
|------------------------|------------------|----------|-----------------|-------------------|----------------|------------------|-------------|
| GPM | LPM | | | | | | |
| 225 | 855 | AL | 2-1/2" ~ 5" THD | 2-1/2" NH | Self-inducting | 1%, 3% | B5801 (ISO) |
| 350 | 1330 | AL | 2-1/2" ~ 5" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5802 (ISO) |
| 500 | 1900 | AL | 2-1/2" ~ 5" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5803 (ISO) |
| 750 | 2850 | AL | 2-1/2" ~ 5" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5804 (ISO) |
| 225, 350, 500 | 855, 1330, 1900 | AL | 2-1/2" ~ 5" THD | 2-1/2" NH | Self-inducting | 1%, 3%, 6% | B5805 (ISO) |
| 350, 500, 750 | 1330, 1900, 2850 | AL | 2-1/2" ~ 5" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5806 (ISO) |
| 225 | 855 | AL | (2) 2-1/2" THD | 2-1/2" NH | Self-inducting | 1%, 3% | B5807 (ISO) |
| 350 | 1330 | AL | (2) 2-1/2" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5808 (ISO) |

Dual-purpose portable ground foam monitor

Available size

| Flow @ 100 psi (7 bar) | | Material | Base inlet | Outlet for nozzle | Nozzle type | Foam concentrate | Ref. No. |
|------------------------|------------------|----------|----------------|-------------------|----------------|------------------|-------------|
| GPM | LPM | | | | | | |
| 500 | 1900 | AL | (2) 2-1/2" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5809 (ISO) |
| 750 | 2850 | AL | (2) 2-1/2" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5810 (ISO) |
| 225, 350, 500 | 855, 1330, 1900 | AL | (2) 2-1/2" THD | 2-1/2" NH | Self-inducting | 1%, 3%, 6% | B5811 (ISO) |
| 350, 500, 750 | 1330, 1900, 2850 | AL | (2) 2-1/2" THD | 2-1/2" NH | Self-inducting | 0.5% ~ 6% | B5812 (ISO) |

Note:

1. For base inlet 2-1/2" to 5" THD, it is available with size 2-1/2", 3", 3-1/2", 4", and 5".
2. For base inlet (2) 2-1/2" THD, it is also available with dual integrated ball shutoff.