



Constant gallonage self-inducting foam monitor nozzle (Brass)

- Certificate: FM Approved
- Standard: NFPA 11, UL 162, GB 19156
- Material: Brass
- Feature: Self-inducting with pick-up tube, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Rough

Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
225	855	Brass	2-1/2" NH	Quick connection	1%, 3%	B6101 (FM)
350	1330	Brass	2-1/2" NH	Quick connection	0.5% ~ 6%	B6102 (FM)
500	1900	Brass	2-1/2" NH	Quick connection	0.5% ~ 6%	B6103 (FM)
750	2850	Brass	2-1/2" NH	Quick connection	0.5% ~ 6%	B6104 (FM)



Constant gallonage self-inducting foam monitor nozzle (Bronze)

- Certificate: UL Listed
- Standard: NFPA 11, UL 162, GB 19156
- Material: Bronze
- Feature: Self-inducting with pick-up tube, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Rough

Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
500	1900	Bronze	3" BSP / NH	1-1/4" BSP	3%	B6201 (UL)
750	2850	Bronze	3" BSP / NH	1-1/4" BSP	3%	B6202 (UL)

Note: It is UL listed when equipped to specific B33 and B49 foam monitor.