



Constant gallonage self-inducting foam monitor nozzle (SS)

- Certificate: UL Listed
- Standard: NFPA 11, UL 162, GB 19156
- Material: SS304 / SS316 / SS316L
- Feature: Self-inducting with pick-up tube, straight jet and wide spray
- W. pressure: 175 psi
- Surface: Shotblasted

Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
500	1900	SS	4" BSP	1-1/4" BSP	3%	B6301 (UL)
750	2850	SS	4" BSP	1-1/4" BSP	3%	B6302 (UL)
1000	3800	SS	4" BSP	1-1/4" BSP	3%	B6303 (UL)

Note: It is UL listed when equipped to specific B38 foam monitor.



Constant gallonage self-inducting foam monitor nozzle (AL / bronze / SS)

- Certificate: UL Listed
- Standard: NFPA 11, UL 162, GB 19156
- Material: Aluminum alloy / bronze / SS
- Feature: Self-inducting with pick-up tube, straight jet and wide spray
- W. pressure: 175 psi
- Surface: Hard anodized / rough / shotblasted

Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
1000	3800	AL / bronze / SS	4" BSP	1-1/4" BSP	3%	B6401 (UL)
1250	4750	AL / bronze / SS	4" BSP	1-1/4" BSP	3%	B6402 (UL)

Note: It is UL listed when equipped to specific B38 foam monitor.