



## Adjustable flow self-inducting foam monitor nozzle (Brass)

- Certificate: FM Approved
- Standard: NFPA 11, UL 162, GB 19156
- Material: Brass
- Feature: Self-inducting with pick-up tube, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Rough

### Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
225, 350, 500	855, 1330, 1900	Brass	2-1/2" NH	Quick connection	1%, 3%, 6%	B6601 (FM)
350, 500, 750	1330, 1900, 2850	Brass	2-1/2" NH	Quick connection	0.5% ~ 6%	B6602 (FM)



## Adjustable flow self-inducting foam monitor nozzle (AL)

- Certificate: ISO
- Standard: NFPA 11, UL 162, GB 19156
- Material: Aluminum alloy
- Feature: Self-inducting with pick-up tube, straight jet and wide spray
- W. pressure: 200 psi
- Surface: Rough

### Available size

Flow @ 100 psi (7 bar)		Material	Water inlet	Foam concentrate inlet	Proportioning	Ref. No.
GPM	LPM					
225, 350, 500	855, 1330, 1900	AL	2-1/2" NH	Quick connection	1%, 3%, 6%	B6701 (ISO)
350, 500, 750	1330, 1900, 2850	AL	2-1/2" NH	Quick connection	0.5% ~ 6%	B6702 (ISO)
300, 500, 750, 1000	1140, 1900, 2850, 3800	AL	2-1/2" NH	Quick connection	3%	B6703 (ISO)
1000, 1250, 1500	3800, 4750, 5700	AL	3-1/2" NH	Quick connection	1%	B6704 (ISO)